

# 一般土木工事用仮設配管仕様

## STK鋼管(S0)

## STK鋼管(S1)

呼径	D: 管外径(mm)	t: 管の厚さ(mm)	L: 長さ(m)	重量(kg)/本	カラー外径
25A(1B)	34.0	2.3	6.0	10.8	39.0
25A(1B)	34.0	2.3	3.0	5.4	39.0
50A(2B)	60.5	2.3	6.0	19.8	66.5
50A(2B)	60.5	2.3	3.0	9.9	66.5
80A(3B)	89.1	2.3	6.0	29.5	97.0
80A(3B)	89.1	2.3	3.0	14.8	97.0
100A(4B)	114.3	2.3	6.0	38.1	122.0
100A(4B)	114.3	2.3	3.0	19.1	122.0
100A(4B)	114.3	3.5	6.0	57.4	122.0
100A(4B)	114.3	3.5	3.0	28.7	122.0
150A(6B)	165.2	2.5	6.0	60.0	174.5
150A(6B)	165.2	2.5	3.0	30.0	174.5
150A(6B)	165.2	3.7	6.0	88.2	174.5
150A(6B)	165.2	3.7	3.0	44.1	174.5
200A(8B)	216.3	3.0	6.0	94.8	228.5
200A(8B)	216.3	3.0	3.0	47.4	228.5
200A(8B)	216.3	4.5	6.0	141.0	228.5
200A(8B)	216.3	4.5	3.0	70.5	228.5
250A(10B)	267.4	3.5	6.0	137.0	279.5
250A(10B)	267.4	3.5	3.0	68.5	279.5
300A(12B)	318.5	6.0	6.0	277.0	330.0
300A(12B)	318.5	6.0	3.0	138.5	330.0